

---

|                                |   |
|--------------------------------|---|
| <b>Model No.</b>               | TempU07TH   |
| <b>Dimension</b>               | 100x 43x 12mm   |
| <b>Weight(s)</b>               | 54g   |
| <b>Temperature Range</b>       | Built-in: -30°C ~ +70°C                                 |
| <b>Accuracy</b>                | Temp:±0.3°C Humidity: ±3%RH                             |
| <b>Memory Capacity</b>         | 34560 data points                                       |
| <b>Start Mode</b>              | Button Start or Timed Start                             |
| <b>Resolution</b>              | Temp:0.1°C Humidity: 0.1%RH                             |
| <b>Usage</b>                   | Multiple times  |
| <b>Battery Shelf Life</b>      | 2 years   |
| <b>Recording Interval</b>      | 10 seconds to 99 hours adjustable [Default: 10 minutes] |
| <b>Start Delay</b>             | Programmable(0~72 hours) [Default: 30 minutes]          |
| <b>Alarm Delay</b>             | Programmable (0~99 hours) [Default: 10 minutes]         |
| <b>Protection Class</b>        | IP65  |
| <b>Communication Interface</b> | USB 2.0   |
| <b>Form of Report</b>          | PDF and CSV format data report                          |